



MODEL No.

200AT-50YC

Cable Cutter

Cutting capacity: up to 50mm cable (including insulation)

of cuts/charge (BP-70MH)

Cu 3×150mm ² (46mmOD)	40
Cu 500mm ² (45mmOD)	34

REMARKS

Cuts nonferrous cables only.



MODEL No.

200AT-S16

Re-bar Cutter

Cutting capacity: # of cuts/charge (BP-70MH)

16mm rebar	120
16mm soft steel bar	120
13mm stainless steel bar	105



MODEL No.

200AT-13WT

Threaded bar Cutter

Cutting capacity: # of cuts/charge (BP-70MH)

W3/8" Soft steel (ss)	105
Stainless	52
W1/2" Soft steel (ss)	82
stainless	42

※ W1/2" Die sold separately



MODEL No.

200AT-9PD

Knock out Puncher

Punching capacity : up to B104 (115.5mm) diameter hole
on 3.2mm thickness mild steel
34/charge (BP-70MH)**REMARKS**

Punch & die, Set bolts, Collars are the same as those used for SH-10.

200AT-9PD comes with Set bolts and Collars.

Punch and die are sold separately. (See SH-10 page)



MODEL No.

200AT-AP18

Angle Steel Puncher

Punching capacity: φ 10.5, φ 13.5, φ 17.5 mm
holes on 6mm thickness steel

Size:	186×130×67 mm
Weight:	3.8 kg
# of punching/charge:	82 (BP-70MH)



MODEL No.

200AT-DCM
(150AT-DCM+200AD-DCM) Raceway Cutter

Applicable raceway	: D-1,S-D1,P-1,D-2
Size	: 176 (H) x200 (W) x108 (D) mm
Weight	: 4.5 kg
# of cutting/charge	: 165/BP-70MH
Cutting speed	: 3 sec.



MODEL No.

200AT-Hex Hexagonal Compression Dies

Compression Dies & # of compression per charge

Size	Across vertex	Die width
Cu8~14-12	12	18.4
Cu22~38-14	14	15
Cu45~70-19	19	11
Cu75~100-23	23	9
Cu110~125-26	26	11
Cu150-29	29	10
Cu180~200-32	32	10

REMARKS

of compression for Cu180~200-32 : 35 (BP-70MH)



MODEL No.

200AT-16B Dies for C-connectors

Compression Dies & # of compression per charge. (BP-70MH)

Size	Size	Size
T-11	T-44	T-122
T-16	T-60	T-154
T-20	T-76	T-190
T-26	T-98	T-240

REMARKS

Dies are the same as those of #16B tool.

of compression for T-240 : 40 (BP-70MH)



MODEL No.

P-200M Multipurpose Hydraulic Head

Maximum input pressure:	68.5Mpa or 10,000 PSI
Oil Volume Required:	40cc
Output force:	124 kN
Weight:	2.8 kg